

Small Bore Stainless Steel Flexible Conduit

T2013

- IP50
- #304 Stainless steel core.
- #316 Stainless steel core is available by request, type T2016, for high corrosion area, e.g. seashore.

T2017

- IP65
- #304 Stainless steel core, RoHS and UL 360 compliant PVC jacketed.
- Liquid-tight, oil-resistant, flame retardant, and sunlight resistant.
- Temperature range: -20°C ~ 70°C
- Color: Black, other colors are available by request.



T2013



T2017

Features

Construction:

- Square-locked
- Extremely small bending radius, high flexibility

Application:

- For the protection of small diameter wire, and fiber optics, such as linear scale and testing equipments



Trade Size (mm)	Catalog Number	Min. I.D. (mm)	Max. I.D. (mm)	Min. O.D. (mm)	Max. O.D. (mm)	Min. Bending Radius (mm)	Packing (m)
3.5 x 5.7	T20130350	3.3	3.7	5.5	5.9	17.5	100
4.0 x 6.2	T20130400	3.8	4.2	6.0	6.4	17.5	100
5.0 x 7.2	T20130500	4.8	5.2	7.0	7.4	17.5	100
6.0 x 8.2	T20130600	5.8	6.2	8.0	8.4	20.0	100
6.5 x 8.7	T20130650	6.3	6.7	8.5	8.9	20.0	100
7.0 x 9.2	T20130700	6.8	7.2	9.0	9.4	20.0	100
7.5 x 9.7	T20130750	7.3	7.7	9.5	9.9	20.0	100
8.0 x 10.2	T20130800	7.8	8.2	10.0	10.4	20.0	100
9.0 x 11.2	T20130900	8.8	9.2	11.0	11.4	22.5	100

Trade Size (mm)	Catalog Number	Min. I.D. (mm)	Max. I.D. (mm)	Min. O.D. (mm)	Max. O.D. (mm)	Min. Bending Radius (mm)	Packing (m)
5.0 X 8.5	T20170500	4.8	5.2	8.3	8.7	25.0	50
6.0 X 9.5	T20170600	5.8	6.2	9.3	9.7	27.5	50
6.5 X 10.0	T20170650	6.3	6.7	9.8	10.2	27.5	50
7.0 X 10.5	T20170700	6.8	7.2	10.3	10.7	32.5	50
7.5 X 11.0	T20170750	7.3	7.7	10.8	11.2	32.5	50
8.0 X 11.5	T20170800	7.8	8.2	11.3	11.7	35.0	50
9.0 X 12.5	T20170900	8.8	9.2	12.3	12.7	35.0	50