

Plastic Flexible Conduit

N2017 | Nylon Flexible Conduit

■ IP65

RoHS



Features

- Material: Polyamide 6 (PA6)(Nylon 6)
- Europe Specification
- Temperature range: -30°C~105°C
- Light , flexible, weather resistant, high impact resistant and high pressure bearing ability
- For machinery, transportation facilities
- Superior sunlight resistance
- Halogen free, self extinguishing, UL 94 V2
- Best performance with fitting B0439/L0439

Trade Size (inch)	Catalog Number	I.D. (mm)	O.D. (mm)	Packing (m)
1/4"	N20170207	6.8	10.0	100
5/16"	N20170209	9.6	13.0	50
3/8"	N20170311	12.0	15.8	50
1/2"	N20170416	16.2	21.2	50
3/4"	N20170621	21.9	28.5	50
1"	N20171029	27.6	34.5	50
1-1/4"	N20171236	36.0	42.5	25
2"	N20172048	47.0	54.5	25

E2017 | PE Flexible Conduit

■ IP65



E2017



E2018

Features

- Material: Polyethylene (PE)
- Temperature range: -30°C ~ 80°C
- Light , flexible, fast installation
- Best performance with fitting B0419/L0419

Trade Size (inch)	Catalog Number	I.D. (mm)	O.D. (mm)	Packing (m)
3/8"	E20170300	13.8	17.8	100
1/2"	E20170400	17.2	22.0	100
3/4"	E20170600	21.2	26.0	100
1"	E20171000	28.7	34.0	50
1-1/4"	E20171200	36.0	42.0	50
1-1/2"	E20171400	40.0	48.0	50
2"	E20172000	52.0	60.0	50