

Liquid-tight Flexible Steel Conduit - BS Type

A2017

- Galvanized steel core
- Third party testing: BSI test approval under BS EN 61386.
- Color: Black, other colors are available by request

A2017-ST

- #304 Stainless steel core
- Color: Black, other colors are available by request



A2018

- Galvanized steel core
- Color: Gray



Features

Construction:

- Square-locked construction, RoHS and UL 360 compliant PVC jacketed.
- Liquid-tight, oil-resistant, flame retardant, and sunlight resistant.
- Temperature range: -20°C ~ 70°C
- Light, excellent flexibility and liquid-tightness.

Application:

- For mass production equipment, machine tools
- For places where wires need to be away from water, oil, gas or dusts and require flexibility
- For all kinds of industrial or commercial applications



Trade Size (inch)	Catalog Number			Min. I.D. (mm)	Max. I.D. (mm)	Min. O.D. (mm)	Max. O.D. (mm)	Min. Bending Radius (mm)	Packing (m)
5/16"	A20170200	A201702ST	A20180200	10.3	10.8	14.3	14.8	35	50
3/8"	A20170300	A201703ST	A20180300	12.3	12.8	16.7	17.2	35	50
1/2"	A20170400	A201704ST	A20180400	15.8	16.3	20.2	20.7	45	50
3/4"	A20170600	A201706ST	A20180600	20.8	21.3	25.6	26.1	50	50
1"	A20171000	A201710ST	A20181000	26.4	27.0	31.6	32.2	75	30
1-1/4"	A20171200	A201712ST	A20181200	34.7	35.4	40.7	41.4	100	25
1-1/2"	A20171400	A201714ST	A20181400	40.1	40.7	46.4	47.0	125	20
2"	A20172000	A201720ST	A20182000	51.3	51.9	58.1	58.7	150	15
2-1/2"	A20172400	A201724ST	A20182400	63.0	63.6	71.8	72.4	175	10
3"	A20173000	A201730ST	A20183000	78.0	78.7	87.2	87.9	200	10
4"	A20174000	A201740ST	A20184000	101.6	102.6	111.2	112.3	265	5