

## Flexible Metal Conduit

### A7012

- Galvanized steel core, not liquid-tight.

### A7013

- #304 Stainless steel core, not liquid-tight
- #316 Stainless steel core is available by request, for high corrosion area, e.g. seashore



### Features

#### Construction:

- Interlocked
- Good tensile property
- Flat and smooth internal surface for better cable installation

#### Application:

- For large machinery or automatic machine which requires heavy bearing and tensile property
- For transportation facility and heavy industry



Trade Size (inch)	Catalog Number		Min. I.D. (mm)	Max. I.D. (mm)	Min. O.D. (mm)	Max. O.D. (mm)	Min. Bending Radius (mm)	Packing (m)
3/8"	A70120300	A70130300	12.3	12.8	15.3	15.8	55	30
1/2"	A70120400	A70130400	15.8	16.3	18.8	19.3	85	30
3/4"	A70120600	A70130600	20.8	21.3	23.8	24.3	110	30
1"	A70121000	A70131000	26.4	27.1	29.4	30.1	150	30
1-1/4"	A70121200	A70131200	35.1	35.8	39.5	40.2	175	15
1-1/2"	A70121400	A70131400	40.1	40.8	44.5	45.2	190	15
2"	A70122000	A70132000	51.3	52.0	55.7	56.4	240	15
2-1/2"	A70122400	A70132400	63.0	63.7	67.4	68.1	310	10
3"	A70123000	A70133000	78.0	78.7	83.0	83.7	380	10
4"	A70124000	A70134000	101.6	102.6	106.6	107.6	490	5